



## RAPTION 150 HC CCS2

RAPTION 150 HC CCS2, Outdoor recharge station

Code: V1762E. (CONSULTAR DISPONIBILIDAD)

- > Communications: Ethernet | 4G
- > Output type: 100-920 Vcc - 250 A - 150 kW | 100-920 Vcc - 250 A - 150 kW
- > Connector type: CCS Combo 2 (FF) | CCS Combo 2 (FF)
- > Grid type: Single-phase
- > No. Sockets: 2
- > Earth leakage protection: Type B

### Specifications

#### AC power supply

Input intensity	228 A
Efficiency	95 % con potencia nominal de salida
Power factor	> 0,98
Frequency	50 / 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ ± 10 %

#### Electrical characteristics

Surge protection (DSP)	Optional: 4-pole transient overvoltage (IEC 61643-11 Class II)
Overcurrent protection	Circuit breaker

#### Mechanical characteristics

Size (mm) width x height x depth	470 x 2070 x 380 (mm)
Envelope	Stainless steel

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Working temperature	-10...+50 °C

#### Standards

Certifications	CE / Combo-2
Standards	(DIN 70121; ISO15118); IEC 61851-1; IEC 61851-23

#### Communications

Protocol	OCPP 1.6 / XML
Type	Ethernet 10/100 Base TX (TCP/IP)

#### User interface

RFID (Radio-Frequency Identification)	ISO / IEC 14443A / B , MIFARE Classic, MIFARE DESFire, MIFARE DESFire EV1 , ISO 18092 / ECMA-340 (NFC) 13.56 MHz
LED	Charging indicator and courtesy lighting



## RAPTION 150 HC CCS2

Quick outdoor charging station

Code: V1762E.

Display type	8" TFT touch screen anti-vandalism display
--------------	--

### Features / performance

Optional	Air-conditioning heater -30 ... +50 °C Vandal-proof protection by mechanical locking of the connector Contactless payment system Connection cables 5.5 m
----------	---

### Protection

Safety relay type (class)	Type B
---------------------------	--------

### Output 1

Maximum current	250 A
Maximum power	150 kW
Voltage range	100 ... 920 Vdc
Network type	DC

### Output 2

Maximum current	200 A
Maximum power	150 kW
Voltage range	100...920 Vdc
Network type	DC



## RAPTION 150 HC CCS2

Quick outdoor charging station

Code: V1762E.

### Dimensions

