



## RAPTION 240C CCS2-CCS2 BC-5M

RAPTION 240C CCS2-CCS2 BC-5M, Compact outdoor fast charging station, mode 4

Code: V17C03.

- > Cable (m): 5.5
- > Communications: Ethernet | 2xSIM 4G | Wi-Fi | GPRS | GSM
- > Output type: 150-920 Vcc - 500 A - 240 kW | 150-920 Vcc - 500 A - 240 kW
- > Connector type: CCS Combo 2 (FF) | CCS Combo 2 (FF)
- > Grid type: Three-phase
- > Charge mode: 4
- > No. Sockets: 2
- > Connector lock: Sí

### Description

The **RAPTION 240C** is a fast charging station for electric vehicles that significantly reduces charging times in short-term car parks. This model has a charging capacity of 240 kW (500 A) in Boost mode, regardless of the battery's working voltage. It also allows charging two EVs simultaneously by offering 120 kW per connector, which provides flexibility and adaptability to the charging needs of both current and future vehicles, thus anticipating market demands.

In addition to its high charging power, the device offers an excellent user experience with a design intended to help people with reduced mobility, thanks to the height of the elements and to the vehicle connection system. It has a 15" anti-vandalism touchscreen that provides a very intuitive interface to interact with the device. It also has LED indicators for the charging status, courtesy lights and the option to install a cable management system, which makes it easier to connect the vehicle charging cables. It also features a contactless payment terminal.

Like all models in the **RAPTION** range, the **RAPTION 240C** is compatible with our dynamic power management system (DLM) to regulate the charge without exceeding the contracted power of the installation. The device has an **OCPP** communication protocol to integrate it with management platforms. It can also be configured as a Master in Master-Slave solutions.

### Application

The **RAPTION 240C** is designed for situations that require charging electric vehicles in a short time, such as service stations, rest areas on motorways, as well as in settings where ultrafast charging solutions are desired, such as designated charging spaces in shopping centres, charging hubs, fleets of professional vehicles, charging trucks and fleets of urban buses, etc.



## RAPTION 240C CCS2-CCS2 BC-5M

Quick outdoor charging station

Code: V17C03.

### Specifications

#### AC power supply

Consumption	258 kVA
Input intensity	415 A
Efficiency	96%
Power factor	> 0,99
Frequency	50 / 60 Hz
Type of network	3P + N + PE
Nominal voltage	400 V ~ (± 10 %)

#### Electrical characteristics

Charging mode	Mode 4
No. of charges	2

#### Mechanical characteristics

Size (mm) width x height x depth	1235 x 1910 x 635 (mm)
Envelope	Stainless steel
Noise	< 70 dB
Fastening	Ground
Ventilation	Air cooling fans
Weight (kg)	575

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-40 ... +60 °C
Working temperature	-30 ... +50 °C

#### Communication Network

Protocol	OCPP 1.6J / 2.0 HW Ready
Technology / Type	Ethernet 10/100 Base TX (TCP/IP)

#### User interface

RFID (Radio-Frequency Identification)	NFC, ISO/IEC 14443A (MIFARE Classic, MIFARE DESFire EV1)
LED	Charging indicator and courtesy lighting
Display type	15" TFT touchscreen anti-vandalism display

#### Standards

Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2, IEC 61851-24, IEC 62196-1, IEC 62196-2, IEC 62196-3, Compatible with CHAdeMO, Meets the CCS specification, DIN
-----------	---



## RAPTION 240C CCS2-CCS2 BC-5M

Quick outdoor charging station

Code: V17C03.

70121. ISO 15118 ready, Directives: 2014/53/EU, 2014/30/EU, 2014/35/EU, Modem 4G complies with CE/RED, Compliant with RoHS 2011/65/EU-2017/2102, Meter complies with 2014/32/EU

### Features / performance

Components	Mechanical connector locking
Energy measurement	Meter MID Class 1, EN 50470-3
Optional	4-pole transient overvoltages (IEC 61643-11 Class II) Contactless payment system: Redsys platform Contactless payment system: Payter platform Compatibility extension RFID Legic: NFC, ISO/IEC 14443A/B, ISO/IEC 15693, ISO/IEC 18092, (Legic Advant, Legic Prime, Sony FeliCA, Calypso) MCCB in power supply

### Protection

Element	Isolation monitoring device Magneto-thermal: tripping curve C
---------	---

### Radio communication

Technology / Type	4G / GPRS / GSM Modem
-------------------	-----------------------

### Output 1

Maximum current	500 A
Maximum power	240 kW
Voltage range	150-920 Vcc
Connector type	CCS Combo 2 (FF) (Cable length 5,5m)
Network type	DC

### Output 2

Maximum current	500 A
Maximum power	240 kW
Voltage range	150-920 Vcc
Connector type	CCS Combo 2 (FF) (Cable length 5,5m)
Network type	DC

### RAPTION 240C

240-kW compact, fast-charging stations

CODE	TYPE	Output type	Connector type	Grid type	Communications	Cable (m)	Connector lock	Cable management
V17C00.	RAPTION 240C CCS2-CCS2	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	4		
V17C01.	RAPTION 240C CCS2-CCS2 BC	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	4	1	
V17C02.	RAPTION 240C CCS2-CCS2 5M	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5.5		



## RAPTION 240C CCS2-CCS2 BC-5M

Quick outdoor charging station

Code: V17C03.

CODE	TYPE	Output type	Connector type	Grid type	Communications	Cable (m)	Connector lock	Cable management
V17C03.	RAPTION 240C CCS2-CCS2 BC-5M	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5	1	
V17C06.	RAPTION 240C CCS2-CCS2 5M-CM	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5		1
V17C07.	RAPTION 240C CCS2-CCS2 BC-5M-CM	150-920 Vcc - 500 A - 240 kW 150-920 Vcc - 500 A - 240 kW	CCS Combo 2 (FF)  CCS Combo 2 (FF)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5	1	1
V17C10.	RAPTION 240C CCS2-CHA	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 200 A - 100 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	4   3,5		
V17C11.	RAPTION 240C CCS2-CHA BC	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 200 A - 100 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	4   3,5	1	
V17C12.	RAPTION 240C CCS2-CHA 5M	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 125 A - 62,5 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5		
V17C13.	RAPTION 240C CCS2-CHA BC-5M	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 125 A - 62,5 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5	1	
V17C16.	RAPTION 240C CCS2-CHA 5M-CM	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 125 A - 62,5 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5		1
V17C17.	RAPTION 240C CCS2-CHA BC-5M-CM	150-920 Vcc - 500 A - 240 kW 150-500 Vcc - 125 A - 62,5 kW	CCS Combo 2 (FF)  JEV5 G105 - CHAdeMO (AA)	Three-phase	Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM	5,5	1	1



## RAPTION 240C CCS2-CCS2 BC-5M

Quick outdoor charging station

Code: V17C03.

### Dimensions

