

URBAN WB T22-C2 63

URBAN WB T22-C2 63, Indoor recharge box

Code: V2062C.

> Communications: Ethernet | WiFi
> Output type: 400 Vca - 63 A - 43 kW
> Input current: 64 A
> Connector type: Type 2 cable
> Grid type: Three-phase
> Charge mode: 3
> No. Sockets: 1
> Earth leakage protection: Type B

Description

The **URBAN WB Gen4** is designed to provide a robust charging solution for public-access environments that is resistant to harsh environmental conditions and potential acts of vandalism. They are available in configurations with dual Type 2 cables or with Type 2 sockets and/or Schuko sockets in different combinations, enabling charging in Mode 1-2 and Mode 3 depending on the selected configuration. They also allow simultaneous charging, with one active socket on each side, in single-phase or three-phase installations. In addition, they incorporate individual electrical protections per socket within an aluminium chassis, simplifying installation and maintenance and ensuring maximum safety.

The **URBAN WB Gen4** adds a 7" display and status LEDs; the display itself shows QR codes for authentication and diagnostics, reducing downtime and offering a multilingual experience.

They also integrate the OCPP protocol for easy connection to management platforms and are compatible with our dynamic load management (DLM) system, which adjusts charging without exceeding the contracted power.

Application

URBAN-WB Gen4 charging posts are especially suited for all types of indoor and outdoor car parks. Applications range from public squares, department stores, airports, vehicle sales and rental companies, private car parks, etc.



URBAN WB T22-C2 63

Smart charging devices

Code: V2062C.

Specifications

AC power supply

Input intensity	63 A
Frequency	50/60 Hz
Type of network	3F + N + PE
Nominal voltage	400 V ~ (± 10%)

Electrical characteristics

Charging mode	Mode 3 (IEC 61851-1)
No. of charges	1

Mechanical characteristics

Size (mm) width x height x depth	382 x 928 x 222 (mm)
Envelope	Aluminio y ABS
Fastening	Pared (Mural)
Weight (kg)	25

Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-40 ... +60 °C
Working temperature	-5 ... +45 °C

Communication Network

Protocol	OCPP 1.6J / 2.0.1 HW Ready
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

User interface

RFID (Radio-Frequency Identification)	ISO/IEC 14443 A/B, FELICA, ISO/IEC 15693 / ICODE
LED	Indicador de carga en color RGB
Display type	LCD Multi-idiomas

Standards

Standards	IEC 61851-1, IEC 61851-21-1, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC

Features / performance

Energy measurement	MID Class B meter, EN 50470-3
Optional	• 4G / GPRS Modem • Terminal de pago Cloud (Marca: Payter, Modelo: Apollo)

Creation date: 01/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



URBAN WB T22-C2 63

Smart charging devices

Code: V2062C.

- Protector contra sobretensión transitoria IEC 61643-1 (Clase II)
- Kit de baja temperatura (-30 °C)

Protection

Element	- MCB (80A) Curva de disparo "C" por toma. - RCD Tipo B por toma.

Output 1

Maximum current	63 A
Maximum power	43 kW
Voltage range	400 Vca
Connector type	Cable Tipo 2 (Longitud del cable 5m)
Network type	Trifásica (CA)

Wireless communication

Band	2,4 GHz
Technology / Type	Wi-Fi

URBAN-WB Gen 4
Intelligent double socket charging boxes

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type	Earth leakage protection	Charge mode	Communications
URBAN-WB Gen4								
V206C2.	URBAN-WB M22 Gen4	2	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase	Type A + 6 mAdc	3	Ethernet | Wi-Fi
V206CA.	URBAN-WB M22-C2 Gen4	2	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase	Type A + 6 mAdc	3	Ethernet | Wi-Fi
V206C3.	URBAN-WB T22 Gen4	2	400 Vac - 32 A - 22 kW	Type 2 socket	Three-phase	Type A + 6 mAdc	3	Ethernet | Wi-Fi
V206C6.	URBAN-WB T22-C2 Gen4	2	400 Vac - 32 A - 22 kW	Type 2 cable	Three-phase	Type A + 6 mAdc	3	Ethernet | Wi-Fi
V206C7.	URBAN-WB T24-MIX Gen4	4 (2)	400 Vac - 32 A - 22 kW | 230 Vac – 32 A – 7,4 kW	Type 2 socket | Schuko	Three-phase	Type A + 6 mAdc	1 | 2 | 3	Ethernet | Wi-Fi
URBAN-WB								
V2062C.	URBAN WB T22-C2 63	1	400 Vca - 63 A - 43 kW	Type 2 cable	Three-phase	Type B	3	Ethernet | WiFi

Miniature circuit breaker and differential protection Type A of 30 mA AC + 6 mA DC per socket, Integrated MID energy measurement, RFID reader for identification and activation recharge - ISO 14443 A/B, Data storage, Ethernet and Wi-Fi communications, 4G communications (optional), OCPP 1.6J and 2.0.1 HW Ready communications protocol, Aprox. weight : 30 kg, IP55 aluminum enclosure - IK10, Dimensions 382x928x222 mm. Cable length of 4 m (depending on model)."

Creation date: 01/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.