



## URBAN-WB CCS2

---

URBAN-WB CCS2, DC Car park boxes

Code: V20710. (CONSULTAR DISPONIBILIDAD)

- > Communications: -
- > Output type: 150 ... 920 Vcc - 70 A - 25 kW
- > Connector type: CCS Combo 2 [FF]
- > Grid type: Three-phase
- > Charge mode: 4
- > No. Sockets: 1
- > Earth leakage protection: Type B

### Description

---

The **URBAN-WB CCS** range is the perfect fast-charging solution for small, private settings. It can be installed on the wall or floor thanks to its two models (wallbox and post). This same compact and robust design is also present in its aluminium enclosure, suitable for all types of environments. The **URBAN-WB CCS** has a DC charging power of 25 kW, thus sidestepping the power limitation imposed by chargers on board electric vehicles with AC charging.

### Application

---

The **Urban CCS** range has been developed to offer a fast-charging solution in environments where there is no high-power electrical infrastructure (small electric vehicle fleets, dealerships, carsharing companies, small private car parks, etc.) to improve the charging speed of electric vehicles without a major investment.



# URBAN-WB CCS2

Smart charging devices

Code: V20710.

## Specifications

AC power supply	
Input intensity	39 A
Efficiency	94%
Power factor	> 0,98
Frequency	50 / 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ (± 10 %) (480 V ~ bajo demanda)

Electrical characteristics	
Surge protection (DSP)	Optional
Overcurrent protection	MCB curve C (50 A)
Cable: Connector type	CCS Combo 2 (5.5-m cable length)
Max. output intensity (A)	0 ... 70 cc
Charging mode	Mode 4
No. of charges	1
Max. output power (kW)	25 (cc)
Voltage	150 ... 920 Vdc

Mechanical characteristics	
Size (mm) width x height x depth	382 x 984 x 236 (mm)
Envelope	Aluminium & ABS
Noise	< 55 dB
Fastening	Wall-mounted
Weight (kg)	55

Environmental characteristics	
Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-40 ... +60 °C
Working temperature	-35 ... +45 °C

Standards	
Certifications	CE
Electrical safety, Installation category	CAT III 300 V
Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2, CE / Combo, DIN 70121, ISO 15118, MID: Class 1 - EN 50470-3

Electrical safety	
Insulation	Double-insulated electric shock protection class II (IEC 61010)



# URBAN-WB CCS2

Smart charging devices

Code: V20710.

## User interface

LED	RGB color charge indicator
-----	----------------------------

## Features / performance

Energy measurement	MID counter Class 1, UNE-EN 50470-3
--------------------	-------------------------------------

## Protection

Safety relay type (class)	RCD B
---------------------------	-------

## Output 1

Maximum current	70 A
Maximum power	25 kW
Voltage range	150-920 Vcc
Connector type	CCS Combo 2 (FF)
Network type	DC

Physical Start/Stop buttons, Weight: 52,6 kg, IP54-IK10 aluminium casing, Dimensions: 984 x 382 x 236 mm. 5,5-m cable length.



## URBAN-WB CCS2

---

Smart charging devices

Code: V20710.

## Dimensions

---

