



## URBAN-WB SLAVE CCS2

---

URBAN-WB SLAVE CCS2, DC Car park boxes

Code: V20740. (CONSULTAR DISPONIBILIDAD)

- > Communications: Ethernet
- > Output type: 152 ... 920 Vcc - 70 A - 25 kW
- > Connector type: CCS Combo 2 [FF]
- > Grid type: Three-phase
- > Charge mode: 4
- > No. Sockets: 1
- > Earth leakage protection: Type B

### Application

---

The **Urban CCS** range has been developed to offer a fast-charging solution in environments where there is no high-power electrical infrastructure (small electric vehicle fleets, dealerships, carsharing companies, small private car parks, etc.) to improve the charging speed of electric vehicles without a major investment.



## URBAN-WB SLAVE CCS2

Smart charging devices

Code: V20740.

### Specifications

#### AC power supply

Input intensity	39 A
Efficiency	94%
Power factor	> 0,98
Frequency	50 / 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ ( $\pm 10\%$ ) (480 V ~ bajo demanda)

#### Electrical characteristics

Surge protection (DSP)	Optional
Overcurrent protection	MCB curve C (50 A)
Cable: Connector type	CCS Combo 2 (5.5-m cable length)
Max. output intensity (A)	0 ... 70 cc
Charging mode	Mode 4
No. of charges	1
Max. output power (kW)	25 (cc)
Voltage	150 ... 920 Vdc

#### Mechanical characteristics

Size (mm) width x height x depth	382 x 984 x 236 (mm)
Envelope	Stainless steel
Noise	< 55 dB
Fastening	Wall-mounted
Weight (kg)	56

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-40 ... +60 °C
Working temperature	-35 ... +45 °C

#### Standards

Certifications	CE
Electrical safety, Installation category	CAT III 300 V
Standards	IEC 61851-1, IEC 61851-22, IEC 61851-23, IEC 62196-1, IEC 62196-2, IEC 62196-3, CHAdeMO Certified, CCS (DIN 70121, ISO 15118)

#### Communication Network

Protocol	OCPP
----------	------



## URBAN-WB SLAVE CCS2

Smart charging devices

Code: V20740.

Technology / Type	Ethernet 10/100 Base TX (TCP/IP)
<b>Electrical safety</b>	
Insulation	Double-insulated electric shock protection class II (IEC 61010)
<b>User interface</b>	
LED	RGB color charge indicator
<b>Features / performance</b>	
Energy measurement	Meter for measuring alternating electrical energy according to UNE-EN 50470
<b>Protection</b>	
Safety relay type (class)	RCD B
<b>Output 1</b>	
Maximum current	70 A
Maximum power	25 kW
Voltage range	150-920 Vcc
Connector type	CCS Combo 2 (FF)
Network type	DC