



eHome T1C16

eHome T1C16, Car park wall box

Code: V25000. (CONSULTAR DISPONIBILIDAD)

> Output type: 230 Vac - 16 A - 3,7 kW

> Input current: 16 A

> Connector type: Type 1 cable > Grid type: Single-phase > Charge mode: 3

Description

> No. Sockets: 1

Designed to be easily installed in both indoor and outdoor private parking spaces, and to be distributed to electric vehicle manufacturers. The eHome range has been optimised to offer the best cost/quality ratio on the market. As a result, we offer a high quality product that can comfortably charge all the electrical vehicle brands on the market in Mode 3 with a Type 1 or Type 2 connector.

Thanks to its compatibility with the CirBEON-63 device, which manages the current supplied to the vehicle based to the power available, the **eHome** charger is ideal for the domestic sector.

Application

Its application focuses on home use, since it is easy to install and comes in a small size.







eHome T1C16

Basic charging wallbox

Code: V25000.

Specifications

AC power supply	
Input intensity	16A
Frequency	50 / 60 Hz
Type of network	1Ph + N + GND
Nominal voltage	230 V ~ (± 10 %)
Electrical characteristics	
Cable: Connector type	Type 1 cable
Max. output intensity (A)	16
Charging mode	Mode 3
No. of charges	1
Max. output power (kW)	3,7
Voltage	230 V ~ (± 10 %)
Mechanical characteristics	
Size (mm) width x height x depth	180 x 315 x 115 (mm)
Envelope	Self-extinguishing ABS-PCVO plastic
Fastening	Wall mounting, 3-point wall anchorage
Weight (kg)	5,36
Environmental characteristics	
Protection class	IP 54 / IK10
Relative humidity (without condensation)	5% 95%
Storage temperature	-40°C +60°C
Working temperature	-5°C +45°C
User interface	
LED	Charge indicator
Standards	
Standards	IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD 2014/30/UE, EMC
Features / performance	
Heating and air conditioning unit	-30 +45 °C (Opcional)

eHome

Home charging stations







eHome T1C16

Basic charging wallbox

Code: V25000.

CODE	TYPE	Output type	Connector type	Grid type
V25030.	eHome T2C32	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase
V25070.	eHome T2S32	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase
V25080.	eHome T2S16 TRI	400 Vac - 16 A - 11 kW	Type 2 socket	Three-phase
V25090.	eHome T2C16 TRI	400 Vac - 16 A - 11 kW	Type 2 cable	Three-phase

End-of-charge light, Compatible with CirBEON-63 sensor, Weight: 3 kg., ABS-PVCO self-extinguishing plastic housing - IPS4 - IK10, Dimensions 315x180x115 mm. 5-m cable length, cable holder included (depending on model).







Circutor

eHome T1C16

Basic charging wallbox

Code: V25000.

Dimensions

Connections





