



eHome T2C16

eHome T2C16, Car park wall box

Code: V25020. (CONSULTAR DISPONIBILIDAD)

> Output type: 230 Vca - 16 A - 3,7 kW

> Input current: 16 A

> Connector type: Type 2 cable> Grid type: Single-phase> Charge mode: 3

> No. Sockets: 1

Description

Designed to be easily installed in both indoor and outdoor private parking spaces, and to be distributed to electric vehicle manufacturers. The eHome range has been optimised to offer the best cost/quality ratio on the market. As a result, we offer a high quality product that can comfortably charge all the electrical vehicle brands on the market in Mode 3 with a Type 1 or Type 2 connector.

Thanks to its compatibility with the CirBEON-63 device, which manages the current supplied to the vehicle based to the power available, the eHome charger is ideal for the domestic sector.

Application

Its application focuses on home use, since it is easy to install and comes in a small size.







eHome T2C16

Basic charging wallbox

Code: V25020.

Specifications

Input intensity	16A		
Frequency	50 / 60 Hz		
Type of network	1Ph + N + GND		
Nominal voltage	230 V ~ (± 10 %)		
Electrical characteristics			
Cable: Connector type	Type 2 cable		
Max. output intensity (A)	16		
Charging mode	Mode 3		
No. of charges	1		
Max. output power (kW)	3,7		
Voltage	230 V ~ (± 10 %)		
Mechanical characteristics			
Size (mm) width x height x depth	180 x 315 x 115 (mm)		
Envelope	Self-extinguishing ABS-PCV0 plastic		
Fastening	Wall mounting, 3-point wall anchorage		
Weight (kg)	2,7		
Environmental characteristics			
Protection class	IP 54 / IK10		
Relative humidity (without condensation)	5% 95%		
Storage temperature	-40°C +60°C		
Working temperature	-5°C +45°C		
User interface			
LED	Charge indicator		
Standards			
Standards	IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD 2014/30/UE, EMC		
Features / performance			
Heating and air conditioning unit	-30 +45 °C (Opcional)		

eHome

Home charging stations







eHome T2C16

Basic charging wallbox

Code: V25020.

CODE	TYPE	Output type	Connector type	Grid type
V25030.	eHome T2C32	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase
V25070.	eHome T2S32	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase
V25080.	eHome T2S16 TRI	400 Vac - 16 A - 11 kW	Type 2 socket	Three-phase
V25090.	eHome T2C16 TRI	400 Vac - 16 A - 11 kW	Type 2 cable	Three-phase

End-of-charge light, Compatible with CirBEON-63 sensor, Weight: 3 kg., ABS-PVCO self-extinguishing plastic housing - IPS4 - IK10, Dimensions 315x180x115 mm. 5-m cable length, cable holder included (depending on model).







Circutor

eHome T2C16

Basic charging wallbox

Code: V25020.

Dimensions

Connections





