



eHome T2C32, Car park wall box

Code: V25030.

> Output type: 230 Vac- 32 A - 7,4 kW

> Input current: 32 A

> Connector type: Type 2 cable > Grid type: Single-phase > Charge mode: 3

> No. Sockets: 1

Description

Designed to be easily installed in both indoor and outdoor private parking spaces, and to be distributed to electric vehicle manufacturers. The eHome range has been optimised to offer the best cost/quality ratio on the market. As a result, we offer a high quality product that can comfortably charge all the electrical vehicle brands on the market in Mode 3 with a Type 1 or Type 2 connector.

Thanks to its compatibility with the CirBEON-63 device, which manages the current supplied to the vehicle based to the power available, the $\ensuremath{\textbf{e}}\xspace\ensuremath{\textbf{H}}\xspace\ensuremath{\textbf{o}}\xspace$ charger is ideal for the domestic sector.

Application

Its application focuses on home use, since it is easy to install and comes in a small size.







Basic charging wallbox

Code: V25030.

Specifications

AC power supply	
Input intensity	32A
Frequency	50 / 60 Hz
Type of network	1Ph + N + GND
Nominal voltage	230 V ~ (± 10 %)
Electrical characteristics	
Cable: Connector type	Type 2 cable
Max. output intensity (A)	32
Charging mode	Mode 3
No. of charges	1
Max. output power (kW)	7,4
Voltage	230 V ~ (± 10 %)
Mechanical characteristics	
Size (mm) width x height x depth	180 x 315 x 115 (mm)
Envelope	Self-extinguishing ABS-PCV0 plastic
Fastening	Wall mounting, 3-point wall anchorage
Weight (kg)	4,4
Environmental characteristics	
Protection class	IP 54 / IK10
Polativo humidity (without condensation)	
Relative humidity (without condensation)	5% 95%
Storage temperature	5% 95% -40°C +60°C
Storage temperature	-40°C +60°C
Storage temperature Working temperature	-40°C +60°C
Storage temperature Working temperature User interface	-40°C +60°C -5°C +45°C
Storage temperature Working temperature User interface LED	-40°C +60°C -5°C +45°C
Storage temperature Working temperature User interface LED Standards	-40°C +60°C -5°C +45°C Charge indicator IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD;
Storage temperature Working temperature User interface LED Standards Standards	-40°C +60°C -5°C +45°C Charge indicator IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD;
Storage temperature Working temperature User interface LED Standards Standards Features / performance	-40°C +60°C -5°C +45°C Charge indicator IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC
Storage temperature Working temperature User interface LED Standards Standards Features / performance Heating and air conditioning unit	-40°C +60°C -5°C +45°C Charge indicator IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC







Basic charging wallbox

Code: V25030.

Voltage range	230 Vca
Connector type	Type 2 cable
Network type	Single-phase (AC)

eHome

Home charging stations

CODE	TYPE	Output type	Connector type	Grid type
V25030.	eHome T2C32	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase
V25070.	eHome T2S32	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase
V25080.	eHome T2S16 TRI	400 Vac - 16 A - 11 kW	Type 2 socket	Three-phase
V25090.	eHome T2C16 TRI	400 Vac - 16 A - 11 kW	Type 2 cable	Three-phase

End-of-charge light, Compatible with CirBEON-63 sensor, Weight: 3 kg, ABS-PVCO self-extinguishing plastic housing - IP54 - IK10, Dimensions 315x180x115 mm. 5-m cable length, cable holder included (depending on model).







Basic charging wallbox

Code: V25030.

Connections Dimensions





