





ePark, Car park boxes

Code: V27100. DESCATALOGADO

> Communications: Ethernet

> Output type: 230 Vca - 32 A - 7,4 kW

> Connector type: Type 2 socket

> Grid type: Single-phase

> No. Sockets: 2

### Description

With a modern and minimalist design, the ePark range is the best smart charging option for multi-user car parks in residential blocks, work places and car parks. This range has several dual-charger models that allow simultaneous charging of two vehicles with both single-phase and three-phase lines, making it the ideal solution for installing charging stations in multi-user car parks and adapting the facilities to the new needs of electric cars.

The minimalist interface, consisting of a display and LEDs to indicate the charging status, provides an intuitive and friendly user experience. This range is compatible with our dynamic power management system (DLM) to regulate the charge without exceeding the contracted power. The device also has an OCPP communications protocol for easy integration with management platforms.

### **Application**

The **ePark** range is designed to manage multiple users in covered car parks who need to recharge their electric vehicles, such as parking areas in residential blocks or condominiums, work places and public car parks.







Electric vehicle charging device

Code: V27100.

## **Specifications**

AC power supply					
Input intensity	32A				
Frequency	50 / 60 Hz				
Type of network	1Ph + N + GND				
Nominal voltage	230 V ~ (± 10 %)				
Electrical characteristics					
Cable: Connector type	Base Type 2				
Max. output intensity (A)	32				
Charging mode	Mode 3				
No. of charges	1				
Max. output power (kW)	7,4kW				
Voltage	230 V ~ (± 10 %)				
Mechanical characteristics					
Size (mm) width x height x depth	335 x 315 x 179.7 (mm)				
Envelope	Plastic ABS / PC				
Fastening	Vertical, 3 points for wall mounting				
Weight (kg)	4				
Environmental characteristics					
Protection class	IP 54 / IK10				
Relative humidity (without condensation)	5 95 %				
Storage temperature	-20 +60 °C				
Working temperature	-5 +45 °C				
User interface					
RFID (Radio-Frequency Identification)	ISO 14443 A/B NFC 13,56 MHz				
LED	RGB color charge indicator				
Display type	Multi-language LCD				
Visible display area size	4"				
Standards					
Standards	IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC62196-2, 2014/35/UE, LVD;2014/30/UE, EMC, ISO 14443A/B				
Features / performance					
Heating and air conditioning unit	-30 +45 °C (Opcional)				
Energy measurement	MID counter				







Electric vehicle charging device

Intelligent chargin boxes

Code: V27100.

#### Thermal-magnetic protection

Trip curve, Type

MCB (Curva C)- incluye bobina de disparo

#### **ePark** Intelligent chargin boxes

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type	Charge mode	Communications	Earth leakage protection
V2724000000C2	ePark M-S2	1	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase	3	Ethernet	
V2722000000C2	ePark M-C2	1	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase	3	Ethernet	
V2724400000C2	ePark M-2S2	2	230 Vac- 32 A - 7,4 kW	Type 2 socket	Single-phase	3	Ethernet	
V2722200000C2	ePark M-2C2	2	230 Vac- 32 A - 7,4 kW	Type 2 cable	Single-phase	3	Ethernet	
V27344.	ePark T-2S2 Gen3	2	400 Vac - 32 A - 22 kW	Type 2 socket	Three-phase	3	Ethernet   WiFi	6 mA dc
V27322.	ePark T-2C2 Gen3	2	400 Vac - 32 A - 22 kW	Type 2 cable	Three-phase	3	Ethernet   WiFi	6 mA dc
V2744000000C2	ePark T-S2	1	400 Vac - 32 A - 22 kW	Type 2 socket	Three-phase	3	Ethernet	
V2742000000C2	ePark T-C2	1	400 Vac - 32 A - 22 kW	Type 2 cable	Three-phase	3	Ethernet	

Integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications (optional), OCPP 1.6 communications protocol, weight: 4 kg, ABS/PC - IPS4 - IK10 casing, dimensions 200x335x315 mm. 5-m cable length, cable holder included (depending on model).







Electric vehicle charging device

Code: V27100.

### **Dimensions**





