

COFRET-VE12-4P-40AS 6DC, Protection box

Code: V4146Q. DESCATALOGADO

- > Módules: 12
- > Poles: 4
- > Surge Protection (SPD): Yes
- > System: Three-phase
- > In (A): 40
- > Key: 1
- > Earth leakage protection: Type A + 6 mADC
- > Circuit breaker protection: 40 A

Description

COFRET boxes are designed to offer electrical protection in compliance with the **ITC-BT-52** standard for infrastructures designed to charge electric vehicles. The devices have a Type A RCCB for direct or indirect exposure protection, and a C-curve circuit breaker to protect the recharging units in the event of overloads or short-circuits. If the installation does not have overvoltage protection, a model is available that includes both permanent and transient surge protection.

Application

The COFRET box is absolutely essential when installing any single-phase electric vehicle charging point.

Circutor



Protection box for single-phase charging points

Code: V4146Q.

Specifications

| AC power supply | | | | | | |
|--|---|--|--|--|--|--|
| Frequency | 50 60 Hz. | | | | | |
| Nominal voltage | 400V ~ +/-5% | | | | | |
| Mechanical characteristics | | | | | | |
| Size (mm) width x height x depth | 270 x 250 x 160 (mm) | | | | | |
| Weight (kg) | 2,5 | | | | | |
| Environmental characteristics | | | | | | |
| Protection class | IP 65 IK 08 | | | | | |
| Relative humidity (without condensation) | 5 95 % | | | | | |
| Installation, location, position. | Indoor | | | | | |
| Storage temperature | - 40 +65 °C | | | | | |
| Working temperature | - 5 +40 °C | | | | | |
| Standards | | | | | | |
| Electrical safety, Maximum height (m) | 2000 | | | | | |
| Electrical safety, Contamination level/class | 2 | | | | | |
| Standards | UNE-EN IEC 61439-1, UNE-EN 50550, UNE-EN 61643-11 | | | | | |
| Differential protection | | | | | | |
| Sensitivity (I∆n), A | 30 mA ~ + 6mA dc | | | | | |
| Thermal-magnetic protection | | | | | | |
| Trip curve, Type | Curva C | | | | | |
| Protection | | | | | | |
| Safety relay type (class) | Class A | | | | | |
| | | | | | | |

COFRET

Protection box for charging points

| CODE | TYPE | Earth leakage protection | Circuit breaker protection | Surge Protection (SPD) | Módules | Poles | Energy meter | Surge Protection (SPD+POP) |
|---------|------------------------|--------------------------|----------------------------------|------------------------------|---------|-------|-----------------|----------------------------------|
| 2 poles | | | protection | (5) 07 | | | | (5) 5+1 61 7 |
| V41231. | COFRET-VE6-2P-20A | Туре А | 20 A | No | 6 | 2 | - | |
| V41232. | COFRET-VE6-2P-20AS | Туре А | 20 A | Yes | 6 | 2 | - | |
| V4123Q. | COFRET-VE8-2P-20AS 6DC | Type A + 6 mADC | 20 A | Yes | 8 | 2 | - | |





Protection box for single-phase charging points

Code: V4146Q.

| CODE | ТҮРЕ | Earth leakage protection | Circuit breaker protection | Surge Protection (SPD) | Módules | Poles | Energy meter | Surge Protection (SPD+POP) |
|------------|---------------------------|--------------------------|----------------------------------|------------------------------|---------|-------|-----------------|----------------------------------|
| V41261. | COFRET-VE6-2P-40A | Туре А | 40 A | No | 6 | 2 | - | |
| V41262. | COFRET-VE6-2P-40AS | Туре А | 40 A | Yes | 6 | 2 | - | |
| 2 poles - | Meter reconnection scheme | 2 | | | | | | |
| V4126X. | COFRET-VE8-2P-40AS REC | Туре А | 40 A | | 8 | 2 | - | Yes |
| 2 poles | | | | | | | | |
| V41266. | COFRET-VE8-2P-40AS-MID | Туре А | 40 A | Yes | 8 | 2 | MID | |
| 4 poles | | | | | | | | |
| V41461. | COFRET-VE12-4P-40A | Туре А | 40 A | No | 12 | 4 | - | |
| V41462. | COFRET-VE12-4P-40AS | Туре А | 40 A | Yes | 12 | 4 | - | |
| v + 1-#UZ. | | 1996 7 | 40 A | 105 | 14 | т | | |

Circutor



Protection box for single-phase charging points

Code: V4146Q.

Dimensions

Connections

×

×

