



CirBEON-16

CirBEON-16, Power dynamic control sensor

Code: V42001. CONSULTAR DISPONIBILIDAD

> Contracted power (kW): 3,68

Application

The CirBEON model must be chosen based on contracted power:

- o 16 A for 3,68 kW
- o 20 A for 4,60 kW
- o 25 A for 5,75 kW
- o 30 A for 6,90 kW
- o 35 A for 8,05 kW
- o 40 A for 9,20 kW
- o 45 A for 10,35 kW
- o 50 A for 11,50 kW
- o 63 A for 14,49 kW







CirBEON-16

Code: V42001.

Specifications

Electrical characteristics		
Insulation voltage between terminals S1-S2	0.72/3 kV	
Environmental characteristics		
Protection class	IP 20	
Mechanical characteristics		
Envelope	Polyester	
Weight (kg)	0,05	
Current measurement circuit		
Transformation ratio	16/0.05 A	
Measurement accuracy		
Accuracy	Clase 1	

CirBEON

Sensor for dynamic recharge power control

CODE	TYPE	Contracted power (kW)
V42009.	CirBEON-63	14,49

Compatible with eHOME series equipment Maximum distance to the recharging equipment 200 m. Polyester encapsulation, IP 20. Dimensions: 60 x 32 mm







CirBEON-16

Code: V42001.

Connections



