

## CirBEON-40

CirBEON-40, Power dynamic control sensor

Code: V42006. (CONSULTAR DISPONIBILIDAD)

> Contracted power (kW): 9,2

### Application

The **CirBEON** model must be chosen based on contracted power:

- 16 A for 3,68 kW
- 20 A for 4,60 kW
- 25 A for 5,75 kW
- 30 A for 6,90 kW
- 35 A for 8,05 kW
- 40 A for 9,20 kW
- 45 A for 10,35 kW
- 50 A for 11,50 kW
- 63 A for 14,49 kW



# CirBEON-40

Code: V42006.

## Specifications

### Electrical characteristics

|  |           |
|--|-----------|
| Insulation voltage between terminals S1-S2 | 0.72/3 kV |
|--|-----------|

### Environmental characteristics

|                  |       |
|------------------|-------|
| Protection class | IP 20 |
|------------------|-------|

### Mechanical characteristics

|             |           |
|-------------|-----------|
| Envelope    | Polyester |
| Weight (kg) | 0,16      |

### Current measurement circuit

|                      |           |
|----------------------|-----------|
| Transformation ratio | 40/0.05 A |
|----------------------|-----------|

### Measurement accuracy


|          |         |
|----------|---------|
| Accuracy | Clase 1 |
|----------|---------|

### CirBEON

Sensor for dynamic recharge power control

| CODE    | TYPE       | Contracted power (kW) |
|---------|------------|-----------------------|
| V42009. | CirBEON-63 | 14,49                 |

Compatible with eHOME series equipment Maximum distance to the recharging equipment 200 m. Polyester encapsulation, IP 20. Dimensions: 60 x 32 mm



## CirBEON-40

Code: V42006.

## Connections

