

## CirBEON-45

---

CirBEON-45, Power dynamic control sensor

Code: V42007.


> Contracted power (kW): 10,35

### Application

---

The **CirBEON** model must be chosen based on contracted power:

- 16 A for 3,68 kW
- 20 A for 4,60 kW
- 25 A for 5,75 kW
- 30 A for 6,90 kW
- 35 A for 8,05 kW
- 40 A for 9,20 kW
- 45 A for 10,35 kW
- 50 A for 11,50 kW
- 63 A for 14,49 kW



## CirBEON-45

Code: V42007.

### Specifications

#### Electrical characteristics

Insulation voltage between terminals S1-S2	0.72/3 kV
--	-----------

#### Environmental characteristics

Protection class	IP 20
------------------	-------

#### Mechanical characteristics

Envelope	Polyester
Weight (kg)	0,07

#### Current measurement circuit

Transformation ratio	45/0.05 A
----------------------	-----------


#### Measurement accuracy

Accuracy	Clase 1
----------	---------

#### CirBEON

Sensor for dynamic recharge power control

CODE	TYPE	Contracted power (kW)
V42001.	CirBEON-16	3,68
V42002.	CirBEON-20	4,6
V42003.	CirBEON-25	5,75
V42004.	CirBEON-30	6,9
V42005.	CirBEON-35	8,05
V42006.	CirBEON-40	9,2
V42007.	CirBEON-45	10,35
V42008.	CirBEON-50	11,5
V42009.	CirBEON-63	14,49



## CirBEON-45

---

Code: V42007.

## Connections

---

