



## CH48

---

CH48, Hour run meter

Code: M14911.

- > Frequency (Hz): 50
- > Display: Visualizador electromecánico
- > Modules: 48x48

### Application

---

- Timers are used to measure time with a simple, easy and reliable system.
- Measurement of start-up and operating times.
- Modification and operating times.
- Production and quantity times.
- Data to provide information about the following



## CH48

Hour run meters

Code: M14911.

### Specifications

#### AC power supply

Frequency	50/60 Hz
Nominal voltage	230 Vca

#### Mechanical characteristics

Size (mm) width x height x depth	48 x 48 x 48 (mm)
Fastening	Panel
Weight (kg)	0,042

#### Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

#### Standards

Certifications	UL
Standards	BS 89, EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318

#### Current measurement circuit

Consumption	10 mA
-------------	-------

#### User interface

Display format	1,5 x 3,5 mm mit lupe
Range	99999,99
Display type	Mechanic

#### CH

Hour run meters

CODE	TYPE	Modules	Frequency (Hz)
M14911.	CH48	48x48	50
M14921.	CH72	72x72	50
M14931.	CH96	96x96	50
M14951.	CH45		50



## CH48

Hour run meters

Code: M14911.

### Dimensions



### Connections

