

eHome RS T2C16 TRI, Car park wall box

Code: V25290. DESCATALOGADO

- > Communications: RS-485
- > Output type: 400 Vac 16 A 11 kW
- > Input current: 16 A
- > Connector type: Type 2 cable
- > Grid type: Three-phase
- > Charge mode: 3
- > No. Sockets: 1

Description

Designed to be easily installed in both indoor and outdoor private parking spaces, and to be distributed to electric vehicle manufacturers. The eHome range has been optimised to offer the best cost/quality ratio on the market. As a result, we offer a high quality product that can comfortably charge all the electrical vehicle brands on the market in Mode 3 with a Type 1 or Type 2 connector.

Thanks to its compatibility with the **CirBEON** device, which manages the current supplied to the vehicle based to the power available, the **eHome** charger is ideal for the domestic sector.

Application

Its application focuses on home use, since it is easy to install and comes in a small size.

Circutor



Basic charging wallbox

Code: V25290.

Specifications

AC power supply Input intensity	16A
	50 / 60 Hz
Frequency	3Ph + N + GND
Type of network	
Nominal voltage	400 V ~ (± 10 %)
Electrical characteristics	
Cable: Connector type	Type 2 cable
Max. output intensity (A)	16
Charging mode	Mode 3
No. of charges	1
Max. output power (kW)	11
Voltage	400 V ~ (± 10 %)
Mechanical characteristics	
Size (mm) width x height x depth	180 x 315 x 115 (mm)
Envelope	Self-extinguishing ABS-PCV0 plastic
Fastening	Wall mounting, 3-point wall anchorage
Weight (kg)	4
Environmental characteristics	
Protection class	IP 54 / IK 10
Relative humidity (without condensation)	95%
Working temperature	-5°C +45°C
User interface	
LED	Charge indicator
Standards	
Standards	IEC 61851-1, IEC 61851-21-2, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE LVD; 2014/30/UE, EMC
Output 1	
Maximum current	16 A
Maximum power	11 kW
Voltage range	400 Vac
Connector type	Type 2 cable
Network type	Three-phase (AC)





Basic charging wallbox

Code: V25290.

End-of-charge light, Compatible with CirBEON sensor, Weight: 4 kg, ABS-PCVO self-extinguishing plastic housing - IP54 - IK10, Dimensions 315x180x115 mm. 5-m cable length, cable holder included (depending on model).

Circutor



Basic charging wallbox

Code: V25290.

Dimensions

Connections

×

×

