



## ePark M-S2

---

ePark M-S2, Car park boxes

Code: V27240. DESCATALOGADO

- > Communications: Ethernet | WiFi
- > Output type: 230 Vca - 32 A - 7,4 kW
- > Connector type: Type 2 socket
- > Grid type: Single-phase
- > Charge mode: 3
- > No. Sockets: 1

### Description

---

With a modern and minimalist design, the **ePark** range is the best smart charging option for multi-user car parks in residential blocks, work places and car parks. This range has several dual-charger models that allow simultaneous charging of two vehicles with both single-phase and three-phase lines, making it the ideal solution for installing charging stations in multi-user car parks and adapting the facilities to the new needs of electric cars.

The minimalist interface, consisting of a display and LEDs to indicate the charging status, provides an intuitive and friendly user experience. This range is compatible with our dynamic power management system (DLM) to regulate the charge without exceeding the contracted power. The device also has an OCPP communications protocol for easy integration with management platforms.

### Application

---

The **ePark** range is designed to manage multiple users in covered car parks who need to recharge their electric vehicles, such as parking areas in residential blocks or condominiums, work places and public car parks.



## ePark M-S2

Electric vehicle charging device

Code: V27240.

### Specifications

#### AC power supply

Input intensity	32 A
Frequency	50/60 Hz
Type of network	1F + N + PE
Nominal voltage	230 V ~ (± 10 %)

#### Electrical characteristics

Charging mode	Mode 3 (IEC 61851-1)
No. of charges	1

#### Mechanical characteristics

Size (mm) width x height x depth	335 x 315 x 179.7 (mm)
Envelope	Plástico ABS-PC
Fastening	Wall fixing with 3 screws
Weight (kg)	3

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Working temperature	-5 ... +45 °C

#### Communication Network

Protocol	OCPP 1.5 /1.6J
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

#### User interface

RFID (Radio-Frequency Identification)	ISO 14443 A/B NFC 13,56 MHz
LED	RGB colour charge indicator
Display type	LCD Multi-idiomas
Visible display area size	4"

#### Standards

Standards	IEC 61851-1, IEC 61851-21-1, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC
-----------	---

#### Features / performance

Energy measurement	MID Class B meter, EN 50470-3
Optional	• 4G / GPRS Modem



## ePark M-S2

Electric vehicle charging device

Code: V27240.

### Output 1

Maximum current	32 A
Maximum power	7,4 kW
Voltage range	230 Vca
Connector type	Type 2 base
Network type	Single-phase (CA)

### ePark

Intelligent charging boxes

CODE	TYPE	Output type	No. Sockets	Connector type	Grid type	Communications	Earth leakage protection	Charge mode
V27540.	ePark M-S2 Gen4	230 Vac - 32 A - 7,4 kW	1	Type 2 socket	Single-phase	Ethernet   WiFi	6 mA CC	3
V27520.	ePark M-C2 Gen4	230 Vac - 32 A - 7,4 kW	1	Type 2 cable	Single-phase	Ethernet   WiFi	6 mA CC	3
V27522.	ePark M-2C2 Gen4	230 Vac - 32 A - 7,4 kW	2	Type 2 cable	Single-phase	Ethernet   WiFi	6 mA CC	3
V27544.	ePark M-2S2 Gen4	230 Vac - 32 A - 7,4 kW	2	Type 2 socket	Single-phase	Ethernet   WiFi	6 mA CC	
V27640.	ePark T-S2 Gen4	400 Vac - 32 A - 22 kW	1	Type 2 socket	Three-phase	Ethernet   WiFi	6 mA CC	3
V27620.	ePark T-C2 Gen4	400 Vac - 32 A - 22 kW	1	Type 2 cable	Three-phase	Ethernet   WiFi	6 mA CC	
V27622.	ePark T-2C2 Gen4	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet   WiFi	6 mA CC	3
V27644.	ePark T-2S2 Gen4	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet   WiFi	6 mA CC	3

Integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications (optional), OCPP 1.6 communications protocol, weight: 4 kg, ABS/PC - IP54 - IK10 casing, dimensions 200x335x315 mm. 5-m cable length, cable holder included (depending on model).



## ePark M-S2

Electric vehicle charging device

Code: V27240.

### Dimensions

