



## UC72 150...500V

UC72 150...500V, Séquencemètres

Code: M13721.

- > Rang mesure (V): 150...500
- > Équipement: UC72
- > Modules: 72x72

### La description

A completely electronic circuit without moving parts allows easily activation of LED

### Application

**UC72** and **UC96** types indicate the phase sequence type in three-phase networks.

**CUC96**, besides indicating the phase sequence type, have a relay with a free voltage switch-over contact.

The relay opens in voltage lack situation or when the phase rotation sense is wrong.



## UC72 150...500V

Code: M13721.

### Spécifications

#### Caractéristiques mécaniques

|                                   |                     |
|-----------------------------------|---------------------|
| Taille (mm) larg. x haut. x prof. | 72 x 72 x 62.9 (mm) |
| Fixation                          | Panneau             |
| Poids (kg)                        | 0,15                |

#### Caractéristiques environnementales

|                         |   |
|-------------------------|---|
| Degré de protection     | Panneau : IP 52 (avant), IP 00 (bornes) |
| Température de stockage | -40 ... +70 °C                          |
| Température de travail  | 0 ... +70 °C                            |

#### Règlementation

|  |  |
|--|--|
| Certifications                             | UL   |
| Sécurité électrique, Altitude maximale (m) | 2000   |
| Règlementation                             | BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318 |

#### Circuit de mesure de courant

|                             |       |
|-----------------------------|-------|
| Consommation                | 3 mA  |
| Fréquence d'échantillonnage | 50 Hz |

#### Circuit de mesure de tension

|                                       |   |
|---------------------------------------|---|
| Tension nominale                      | 230 Vca (en option 100-120 Vca / 380-440 Vca)   |
| Tension maximale de mesure permanente | 1,2 Vn permanent rated voltage / 2 Vn during 5s |

#### Précision de mesure

|           |          |
|-----------|----------|
| Précision | 1,5 % FE |
|-----------|----------|

#### UC / CUC

Séquencemètres


| CODE    | TYPE             | Modules | Équipement |
|---------|------------------|---------|------------|
| M13726. | UC72 100...150V  | 72x72   | UC72       |
| M13721. | UC72 150...500V  | 72x72   | UC72       |
| M13736. | UC96 100 ...150V | 96x96   | UC96       |
| M13731. | UC96 150...500V  | 96x96   | UC96       |
| M13754. | CUC96 230V       | 96x96   | CUC96      |
| M13755. | CUC96 400V       | 96x96   | CUC96      |



# UC72 150...500V

Code: M13721.

## Dimensions



## Connexions

