,

Code:

La description

Magnet Right-Angle Adapter.
Insulated 4 mm Banana (female).
Jack to 6.6 mm diameter.

Application

Optimum safety thanks to the insulation of the overall length of the magnet and its barrier which reminds the forbidden area. Dedicated to semitemporary measuring of voltages onto steel screw terminal blocks. Fast connecting and disconnecting to terminal block thanks to magnet. Safety and preciseness putting thanks to its handle. Access to deep terminal blocks in cluttered environment thanks to the length and fineness of the stick.

Code:

Spécifications

Règlementation

Sécurité électrique, Catégorie d'installation	1000 V CAT II / 1000 V CAT III / 600 V CAT IV
Sécurité électrique, Degré de contamination	Degré de pollution 2

Sécurité électrique

Classe d'isolement	Isolation renforcée

Caractéristiques mécaniques

Poids (kg)	0,036

Date de création: 15/10/2026 - CIRCUTOR, SAU se réserve le droit d'effectuer des changements techniques ou de modifier le contenu/les images de ce document sans préavis, afin d'améliorer sa fiabilité, sa fonctionnalité, sa conception ou pour d'autres raisons.
Elle n'accepte aucune responsabilité pour les erreurs, les inexactitudes ou le manque éventuel d'informations dans ce document.