



MC72 .../5A 120%

MC72 .../5A 120%, Amperímetro máxímetro bimetálico, panel 72x72

Código: M15521. **DESCATALOGADO**

- > Escala: 90°, P1, 2
- > Precisión: 3
- > Rango medida (A): .../5 A
- > Módulos: 72x72

Especificaciones

Mechanical characteristics

Size (mm) width x height x depth	72 x 72 x 49.2 (mm)
Fastening	Panel
Weight (kg)	0,14

Environmental characteristics

Protection class	Panel: IP 52 (Frontal), IP 00 (Terminales)
Storage temperature	-25 ... +40 °C
Working temperature	+10 ... +30 °C

Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

Current measurement circuit

Consumption	3,25 VA
Allowable overload	1,5 In permanente / 15 In durante 1s

Electrical characteristics

Insulation voltage, circuit	2 KV A 50 HZ < 1min entre mecanismo y caja
-----------------------------	--

Measurement accuracy

Accuracy	± 3 % FE
----------	----------

MC
Amperímetros máxímetros

CÓDIGO	TIPO	Escala	Precisión	Rango medida (A)	Módulos
M12231.	MC96 .../5 A	90°, P1, 2	3	.../5 A	96x96
M15531.	MC96 .../5A 120%	90°, P1, 2	3	.../5 A	96x96

Escala NO incluida



MC72 .../5A 120%

Código: M15521.

Conexiones

